



## EIB/KNX Certified 2x2x0,80 Cca LSZH

KNX Cable 2 pairs, Halogen Free

Image representative of cable family. Actual cable may vary.

### Certified by KNX Association

Certificate Nr. 607/19791/23

CPR Class Cca s1,d1,a1

FlameSmart technology

Exceeds cable types  
YCYM, J-Y(St)Y & J-H(St)H



### STANDARDS AND CERTIFICATES

Standards	KNX specification v2.1 EN 50090 EN 50575
KNX Certification	607/19791/23
CPR Class	Cca s1,d1,a1
DOP	1002723
ROHS II	complies

### CONSTRUCTION

Conductors	Φ 0,80mm solid copper
Insulation	HFFR
Laying up	4 cores twisted to quad
Core Identification	Red, Black, Yellow, White
Screen	aluminum tape + drain wire
Outer Sheath	Φ 6,60mm HFFR green

### ELECTRICAL CHARACTERISTICS

Loop Resistance DC	<75,0 Ohm/km
Insulation Resistance	>100 Mohm.km
Mutual Capacitance	<100 pF/m
Test Voltage, core-sheath	4 KV AC 1 min
Operating Voltage	300 V peak

### MECHANICAL CHARACTERISTICS

Minimum bending radius	65 mm
Operating Temperature Range	-20 C to +70 C
Standard packaging	5x100m, 1x500m

Pentalofos, T. 2310 787202  
P.O.Box 10229  
54012 Thessaloniki - Greece  
welcome@accordia.gr  
www.accordia.gr