



EIB/KNX Certified 2x2x0,80 Eca PVC

KNX Cable 2 pairs

Image representative of cable family. Actual cable may vary.

Certified by KNX Association

Certificate Nr. 607/21318/25

CPR certified

Exceeds cable types
YCYM, J-Y(St)Y & J-H(St)H



STANDARDS AND CERTIFICATES

Standards	KNX specification v2.1 EN 50090 EN 50575 607/21318/25 Eca 1002747 complies
KNX Certification	
CPR Class	
DOP	
ROHS II	

CONSTRUCTION

Conductors	Φ 0,80mm solid copper
Insulation	PE
Laying up	4 cores twisted to quad
Core Identification	Red, Black, Yellow, White
Screen	aluminum tape + drain wire
Outer Sheath	Φ 6,10mm PVC green

ELECTRICAL CHARACTERISTICS

Loop Resistance DC	<75,0 Ohm/km
Insulation Resistance	>100 Mohm.km
Mutual Capacitance	<100 pF/m
Test Voltage, core-sheath	4 KV AC 1 min
Operating Voltage	300 V peak

MECHANICAL CHARACTERISTICS

Minimum bending radius	65 mm
Operating Temperature Range	-20 C to +70 C
Standard packaging	5x100m, 1x500m

Pentalofos, T. 2310 787202
P.O.Box 10229
54012 Thessaloniki - Greece
welcome@accordia.gr
www.accordia.gr